## THE SAFEST IN MATERIAL HANDLING











safexelectromech.com

www.safexelectromech.com



Plot No.7608, Phase-IV, G.I.D.C., Vatva, Ahmedabad-382 445, Gujarat, INDIA
Phone: +91 - 79 - 3291 8913, 2584 0513, 2584 1915 Fax: +91 - 79 - 2584 0124
E-mail: scbhatia@safexelectromech.com / info@safexelectromech.com Web: www.safexelectromech.com

EXCELLENT DESIGN
EFFICIENT OPERATION
EFFECTIVE SERVICE
ECONOMICAL OPTIONS

Safex Electromech offers advanced features in a wide range of high quality products developed over 25 years with continual technological innovation. Our products are proven in performance and reliability for various applications and across diverse industrial sectors.





#### **PRODUCT RANGE**











**Material Elevators** 

- ✓ Oil & Gas
- ✓ Petro Chemical
- √ Pharmaceutical
- ✓ Steel Plant
- www.safexelectromech.com
- ✓ Engineering

SA CELECTROMECH

- ✓ Power & Energy
- **INDUSTRIES SERVED**
- Aviation

Automotive

- Shipyards
- √ Food
- √ Fertilizers
- √ Paper & Pulp

## **Street**



www.safexeled

Safex Electromech Pvt. Ltd. has an alliance with Street Crane Company, U.K. The entire range of Street Cranes & Hoists is available.

# **KX** EOT Cranes for Explosive Areas



up to 100 tonnes Capacity:

Lift: up to 60 mtrs.

Speeds: single speed

double speed

micro speed

Type: overhead

> underslung goliath

jib

	CODE FOR USERS	•
Subject	Gas	Dust
immable Data	IS/IEC 60079 -20	IEC 61241 -2-1,2&3
e Cassification	S'IEC 60079 -10-1	IEC 60777 10-1
ection & allation	IS/IEC	60079 -14
pection & intenance	IS/IEC	60079 -17
pair & Overhaul	IS/IEC	60079 -19

	ı	Electrical	Protect	ion Concept	;	-
		Stan	dard			
Ty	pe	IEC/EN/IS	IEC/EN	Protection Concept	L	one
Gas	Dust	Gas	Dust		Gas	Dust
		6007	79-0	General Requirements		
Ex d		60079-1		Flameproof	1	
	Ex taD Ex tbD Ex tcD		60079-31	Dust Ignition Protected Enclosure		20 21 22
Ex px Ex py Ex pz	Ex pD	60079-2	61241-2	Pressurized	1 1 2	21/22
Ex q		60079-5		Powder Filled	1	
Ex o		60079-6		Oil Filled	1	
Exe		60079-7		Increased Safety	1	
Ex ia Ex ib Ex ic	Ex iaD Ex ibD Ex icD	60079-11	61241-11	Intrinsic Safety	0 1 2	20 21 22
Ex nC	lec	60079-15	nec	For -Sparkin : Limited Eversy Restricted Breathing Enclosed Break	2	
Ex Ex Ex	mb	6007	79-18	Encapsulation	0 1 2	20 21 22



Suitable for: Zone 1, Gas Group IIA, IIB & Zone 2, Gas Group IIA, IIB, IIC



## Safex Electromech Electric Wire Rope Hoists

Standard range of hoists

Cost effective range of hoists

Premium range of hoists

Explosion proof hoists for Zone -1 & 2, Zone -22, Gas Gr. IIA, IIB, IIC

KS, KP, KX Hoists are available with Œ

marking

KS Electric Wire Rope Hoists use modular construction conforming to IS: 3938 & are available with standard features



KS010H	500	IV	2/1	6	4	15	140	
KS010J	625	Ш	2/1	6	4	15	150	
KS0101	1000	IV	2/1	6	4	15	180	
KS010K	1250	Ш	2/1	6	4	15	195	
KS0202	2000	Ш	2/1	6	3	15	350	
KS0242	2000	IV	4/2	6	3	15	380	
KS020L	2500	Ш	2/1	6	3	15	400	
KS0303	3000	Ш	2/1	6	3	15	450	
KS0343	3000	IV	4/2	6	3	15	475	
KS0305	5000	IV	4/2	6	3	15	560	
KSC30IA	6250	.GO	1/2	6	2.5	V-158	116 <sub>576</sub> e	ĮΘ
KS0475	7500	III	4/2	6	3	15	1050	
KS0410	10,000	П	4/2	6	3	15	1150	
KS0412	12,500	П	4/2	6	3	15	1200	
KS0415	15,000	Н	4/2	6	2.5	15	1350	
KS0515	15,000	III	4/2	6	3	15	1500	
KS0520	20,000	Ш	4/2	6	2.5	15	1650	
KS0625	25,000	III	8/2	6	2	15	1650	
KS0630	30,000	п	8/2	6	2	15	1800	



A wide range of standard & custom built models to meet the requirements of various industries & applications.

- Higher lift up to 60 mtrs.
- Higher hoisting speed up to 12 mpm.
- Lower CT speed up to 2 mpm.
- Micro hoisting & CT speeds
- Flexible trolley for curved track

# **KP** Premium Range Hoists

The result of over 40 years of design expertise and continuous development

- Hardened & ground hoist gear boxes
- Oil bath lubrication of gears & pinions
- Hoist brake on gear box input shaft and not on motor shaft for increased safety
- Load remains in position with brake on even when removing motor for maintenance
- Silent operation

**KP** Hoists offer unbeaten performance in a wide range of proven designs



Safe Operation - The one standard focused on by SAFEX ELECTROMECH

## **KX** Hoists for Explosive Areas



### Safex Electromech EOT Cranes

Available with electrical components housed in flame proof enclosures confirming to IS-2148, and mechanical components designed with spark proofing features



250Kg to 50,000 Kgs Capacity: Lift: 6 mtrs. to 60 mtrs.

Hoisting Speeds: 3, 4, 6, 8, 10 mpm.

3/0.7, 4/1, 8/2, 10/2.5 mpm.

• Micro Speed: .3, .4, .6, .8, 1 mpm.

CT speed: 10, 15, 20 mpm.

10/2.5, 15/3.7, 20/5 mpm.

Travel: straight path

curvey www.satexelectro cn.com

Type: power travel

> hand travel fix suspension

Suitable for:

Zone 1, Gas Group IIA, IIB Zone 2, Gas Group IIA, IIB, IIC

Area Classification			
Gas	Dust	Hazardous Area	
Zone 0	Zone 20	Frequently Present	
Zone 1	Zone 21	Present in Normal Condition	
Zone 2	Zone 22	Present in Abnormal Condition	

	GAS GROUP
Gas Group	Representative Test Gas
1	Methane (Mining only)
IIA	Propane
IIB	Ethylene
IIC	Hydrogen
Gases are cla	ssified according to ignitability

of gas-air mixture. Refer IEC/EN/IS 60079-20

DUST GROUP		
Dust Group	Type of Combustible Dust	
IIIA	Combustible Flying Dust	
IIIB	Non - conductive Dust	
IIIC	Conductive Dust	

#### FLP Electricals with CMRI / CCOE / PESO / ATEX Certifications











Flame Proof Brake

Safex Electromech Electric Overhead Traveling Cranes are available in various designs up to 100 tonnes capacity, 34 mtrs. span and 60 mtrs. height of lift.

We offer infinite solutions adapted to meet customers' requirements. Our unique design is made to suit different needs and stringent dimensional requirements for hook approach, headroom, end clearances, etc.



**Double Girder Cranes** 



**Under Slung Cranes** 



**Goliath Cranes** 



Jib Cranes

